

8G
THE EIGHTH
GENERATION

STARTRAC

COMPACT TRACTORS



Powered by
 **MITSUBISHI**
DIESEL ENGINE

263 HST

8G
THE EIGHTH
GENERATION

Powered by
**MITSUBISHI
DIESEL ENGINE**



STARTRAC

COMPACT TRACTORS



Engine: Stage V
Mitsubishi
3 Cylinders

Opening
Bonnet

750Kg Lifting
Capacity



| SPECIFICATIONS | | STARTRAC 263 HST (Agricultural Tyres) | STARTRAC 263 HST (Turf Tyres) | STARTRAC 263 HST (Industrial/Flotation Tyres) | STARTRAC 263 HST (Agricultural Wide Tyres) | STARTRAC 263 HST (Galaxy Garden Pro Tyres) | STARTRAC 263 HST (Wider F-Agri Tyres) |
|-----------------------|---|---|----------------------------------|--|---|---|--|
| Engine | Engine Horse Power Ps (kW) | 25 (18.2) | | | | | |
| | Engine : Type | Mitsubishi Stage-V : Naturally Aspirated | | | | | |
| | No. of Cylinder | 3 | | | | | |
| | Capacity (CC) | 1319 | | | | | |
| | Rated Speed (RPM) | 2500 | | | | | |
| | Cooling System | Liquid Cooled | | | | | |
| | Bore / Stroke (mm) | 78/92 | | | | | |
| Max Torque (Nm) @ RPM | 76.3 (Nm) @ 2000 RPM | | | | | | |
| Tyres | Front | 180/85D12 | 23 x 8.5 - 12 | 23 x 8.5 - 12 | 6.5/80-12 | 220/55R12 | 23 x 8.5 - 12 |
| | Rear | 8.30 x 20 | 33 x 15.5 - 16.5 | 33 x 15.5 - 16.5 | 280/70R18 | 280/70R16 | 280/70R18 |
| Transmission | Type | Hydrostatic | | | | | |
| | Gears | 3 Forward, 3 Reverse (Options of High, Medium or Low Gear) | | | | | |
| | Speed (km / hr.) | 0 to 22.02 | 0 to 20.61 | 0 to 21.30 | 0 to 21.00 | 0 to 19.60 | 0 to 21.00 |
| | PTO RPM | Rear 540 @2406 ERPM / Mid 2000 @2430 ERPM | | | | | |
| | Steering | Hydrostatic Power Steering | | | | | |
| Brake Type | Multi Disc Oil Immersed | | | | | | |
| Hydraulic | Hydraulic System | Auto Draft Sensing & Depth Control (2 Levers) | | | | | |
| | Lift Capacity (kgs.) | 750 (at Lower Link Point) | | | | | |
| | No. of Pumps | 2 (One for Hydrostatic Steering & Unit, Other for Hydraulic System) | | | | | |
| Auxiliary Hydraulics | 1 DA Auxiliary Hydraulics with 2 QRCs (Optional Kit Available : Extra Secondary DA Auxiliary Hydraulics with 2 more QRCs) | | | | | | |
| Dimensions# | Size LxWxH (mm) | 2780* x 1140 x 2060 | 2780* x 1490 x 2040 | 2780* x 1490 x 2043 | 2780* x 1200 x 2040 | 2780* x 1260 x 2005 | 2780* x 1220 x 2040 |
| | Wheel Base (mm) | 1550 | 1550 | 1550 | 1550 | 1550 | 1550 |
| | Rear Track Center (mm) | 811 to 988 | 1080 | 1080 | 845 to 988 | 935 | 845 to 988 |
| | Weight (kg) | 1050 | 1092 | 1120 | 1052 | 1059 | 1056 |

*Dimensions are with Standard Lower Links, it may vary with longer linkages.

#+/- 5% Tolerance variations

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.

